

## Version History

1.00 Original version. Free 1yr HackerGuardian and HackerProof offers.

## 1. Request

The request should be POSTed (rather than GETed) to the above URL.

Required variables are in **bold**.  
Optional variables are in *italics*.

Variable Name (case insensitive)	Type	Max. Length	Description
<b>loginName</b>	string	64 chars	Account Username (case sensitive).
<b>loginPassword</b>	string	128 chars	Account Password (case sensitive).
<b>orderNumber</b>	string	128 chars	The Order Number for an SSL Certificate which qualifies for the Free Upgrade offer.
<b>offerCode</b>	string	64 chars	The required offer. Allowed values are: <b>FREE_HG_UPGRADE</b> = Free 1yr HackerGuardian offer. <b>FREE_HP_UPGRADE</b> = Free 1yr HackerProof offer.
<i>sendConfirmationEmail</i>	integer		<b>0</b> = Don't send an Order Confirmation Email. <b>1</b> = Send an Order Confirmation Email to the Applicant (i.e. the Web Host Reseller). <b>2</b> (the default) = Send an Order Confirmation Email to the Customer (i.e. <i>customerEmailAddress</i> ). <b>3</b> = Send an Order Confirmation Email to both the Applicant and the Customer.
<i>isReturningCustomer</i>	char		<b>Y</b> = An account identified by <i>customerLoginName</i> already exists and should be reused. <b>N</b> (the default)= A new customer account is required.
<i>customerTitle</i>	string	64 chars	The customer's title (e.g. Mr, Mrs, Dr, etc).
<i>customerForename</i>	string	64 chars	The customer's first name.
<i>customerSurname</i>	string	64 chars	The customer's last name.
<b>customerEmailAddress</b>	string	255 chars	The customer's email address.
<b>customerTelephoneNumber</b>	string	32 chars	The customer's telephone number.
<i>customerFaxNumber</i>	string	32 chars	The customer's fax number.
<b>customerLoginName</b>	string	64 chars	The customer's username (case sensitive).
<b>customerLoginPassword</b>	string	128 chars	The customer's password (case sensitive).

Note 1: Before you can use this API, your Web Host Reseller account must also have Reseller capabilities.

## 2. Response

The MIME type will be `application/x-www-form-urlencoded`, because the format of the response will be the same "URL-encoded" format as the request (e.g. `name1=value1&name2=value2`).

Variable Name (case insensitive)	Type	Description
<b>errorCode</b>	integer	Error code (see list below for possible values).
<i>orderNumber</i>	string	The Order Number for the Free offer (if it was granted). This will normally be the same as the original Order Number with "hgup" or "hpup" appended.
<i>errorMessage</i>	string	Explanation of error.
<i>errorItem</i>	string	The problematic request parameter (this is relevant to errorCode -2, -3 and -4).

Here are the possible values for "errorCode" and "errorMessage":

errorCode	errorMessage
0	Successful
-1	Request was not made over HTTPS!
-2	'xxx' is an unrecognized argument!
-3	The 'xxx' argument is missing!
-4	The value of the 'xxx' argument is invalid!
-14	An unknown error occurred!
-16	Permission Denied for <reason>! Contact Support
-17	Request used GET rather than POST!