

Version History

- 1.00 Original version.
 1.01 Added: Documented the *hasCustomerAgreedToTheTsAndCs* request parameter.
 1.02 Added: The *contactEmailAddress* request parameter.

1. Request

Required variables are in **bold**.
 Optional variables are in *italics*.

Variable Name (case insensitive)	Type	Max. Length	Allowed Values
loginName	string	64 chars	The case-sensitive Username of any user in the Account that applied for the order referenced by "orderNumber" or "foreignOrderNumber".
loginPassword	string	128 chars	The case-sensitive Password associated with "loginName".
<i>saspSessionID</i>	string	16 chars	If this parameter is specified, "loginName" and "loginPassword" should not be specified.
orderNumber	string	128 chars	The Comodo-defined Order Number for which these EV details are being provided.
<i>foreignOrderNumber</i>	string	64 chars	A number for this order, defined by the Applicant and already communicated to Comodo. (If specified, "orderNumber" can be omitted).
incorporatingAgency	string	256 chars	The name of the Applicant's Incorporating Agency.
mainTelephoneNumber	string	32 chars	The main Telephone Number for the Applicant's Place of Business.
certReqTitle	string	64 chars	Certificate Requester's Title or Position.
certReqForename	string	64 chars	Certificate Requester's Forename.
certReqSurname	string	64 chars	Certificate Requester's Surname.
certReqTelephoneNumber	string	32 chars	Certificate Requester's Direct Telephone Number.
certReqEmailAddress	string	255 chars	Certificate Requester's Email Address.
<i>certReqPostOfficeBox</i>	string	40 chars	Certificate Requester's P.O.Box.
certReqStreetAddress1	string	128 chars	Certificate Requester's Street Address 1.
<i>certReqStreetAddress2</i>	string	128 chars	Certificate Requester's Street Address 2 (if required).
<i>certReqStreetAddress3</i>	string	128 chars	Certificate Requester's Street Address 3 (if required).
certReqLocalityName	string	128 chars	Certificate Requester's City or Town.
certReqStateOrProvinceName	string	128 chars	Certificate Requester's State or Province.
certReqPostalCode	string	40 chars	Certificate Requester's Postal Code.
certReqCountryName	string	2 chars	Certificate Requester's Country Name (2-character ISO3166 code).
certReqRelationship	string	256 chars	Certificate Requester's relationship to the Applicant Organization.
certAppTitle	string	64 chars	Certificate Approver's Title or Position.
certAppForename	string	64 chars	Certificate Approver's Forename.
certAppSurname	string	64 chars	Certificate Approver's Surname.
certAppTelephoneNumber	string	32 chars	Certificate Approver's Direct Telephone Number.
certAppEmailAddress	string	255 chars	Certificate Approver's Email Address.
<i>certAppPostOfficeBox</i>	string	40 chars	Certificate Approver's P.O.Box.
certAppStreetAddress1	string	128 chars	Certificate Approver's Street Address 1.
<i>certAppStreetAddress2</i>	string	128 chars	Certificate Approver's Street Address 2 (if required).
<i>certAppStreetAddress3</i>	string	128 chars	Certificate Approver's Street Address 3 (if required).
certAppLocalityName	string	128 chars	Certificate Approver's City or Town.
certAppStateOrProvinceName	string	128 chars	Certificate Approver's State or Province.
certAppPostalCode	string	40 chars	Certificate Approver's Postal Code.
certAppCountryName	string	2 chars	Certificate Approver's Country Name (2-character ISO3166 code).
certAppRelationship	string	256 chars	Certificate Approver's relationship to the Applicant Organization.
contSigTitle	string	64 chars	Contract Signer's Title or Position.
contSigForename	string	64 chars	Contract Signer's Forename.
contSigSurname	string	64 chars	Contract Signer's Surname.
contSigTelephoneNumber	string	32 chars	Contract Signer's Direct Telephone Number.
contSigEmailAddress	string	255 chars	Contract Signer's Email Address.
<i>contSigPostOfficeBox</i>	string	40 chars	Contract Signer's P.O.Box.
contSigStreetAddress1	string	128 chars	Contract Signer's Street Address 1.
<i>contSigStreetAddress2</i>	string	128 chars	Contract Signer's Street Address 2 (if required).
<i>contSigStreetAddress3</i>	string	128 chars	Contract Signer's Street Address 3 (if required).
contSigLocalityName	string	128 chars	Contract Signer's City or Town.
contSigStateOrProvinceName	string	128 chars	Contract Signer's State or Province.
contSigPostalCode	string	40 chars	Contract Signer's Postal Code.
contSigCountryName	string	2 chars	Contract Signer's Country Name (2-character ISO3166 code).
contSigRelationship	string	256 chars	Contract Signer's relationship to the Applicant Organization.
<i>hasCustomerAgreedToTheTsAndCs</i>	char		Y = The customer has been shown and has agreed to the terms of the clickthrough EV Agreement. N = Customer must fill out, sign and send hard copies, available on http://support.comodo.com in the EV Downloads section.
<i>contactEmailAddress</i>	string	255 chars	If specified, this email address will be the only email address that Comodo Validation Staff will correspond with during the processing of this order.

2. Response (when *responseFormat=0*, the default)

2.1 MIME Type

Line	Possible Value(s)
<i>Mime-Type</i>	application/x-www-form-urlencoded

2.2 Parameters

bold when always present.

italic when not always present.

Name	Possible Value(s)
errorCode	An integer (see table below for the possible values).
<i>errorMessage</i>	A string (see table below for the possible values). This parameter is not present when <i>errorCode=0</i> .

Here are the possible values for “errorCode” and “errorMessage”:

errorCode	errorMessage
0	Successful
-1	Request was not made over HTTPS!
-2	' <i>xxxx</i> ' is an unrecognized argument!
-3	The ' <i>xxxx</i> ' argument is missing!
-4	The value of the ' <i>xxxx</i> ' argument is invalid!
-7	' <i>xx</i> ' is not a valid ISO-3166 country!
-14	An unknown error occurred!
-16	Permission denied!
-17	Request used GET rather than POST!