

# <https://secure.comodo.net/products/!ResendDCVEmail>

## Version History

- 1.00 Original version.
- 1.01 Added: "dcvTemplateID" parameter.
- 1.02 Added: "baseOrderNumber" parameter.

## 1. Request

The request should be POSTed (rather than GETed) to the above URL.

Required variables are in **bold**.

Optional variables are in *italics*.

Variable Name (case insensitive)	Type	Max. Length	Description
<b>loginName</b>	string	64 chars	Account Username (case sensitive).
<b>loginPassword</b>	string	128 chars	Account Password (case sensitive).
<i>orderNumber</i> (either "orderNumber" or "baseOrderNumber" must be provided)	integer		The Order Number of a certificate for which Domain Control Validation (DCV) is now required.
<i>baseOrderNumber</i> (either "orderNumber" or "baseOrderNumber" must be provided)	integer		Any base order number previously returned to your account.
<i>dcvEmailAddress</i>	string	255 chars	The email address to which the DCV email should now be sent. This email address must have been returned by a call to the !GetDCVEmailAddress API within the last 24 hours. This parameter may be omitted if the DCV email has been sent previously, in which case the DCV email will be resent to the same email address to which it was last sent.
<i>dcvTemplateID</i>	integer		If specified, this overrides Comodo's default choice of DCV email template to be used to validate this certificate. Talk to your account manager if you would like to set up one or more of your own DCV email templates that can be referenced by this parameter.

## 2. Response

The MIME type will be `application/x-www-form-urlencoded`, because the format of the response will be the same "URL-encoded" format as the request (e.g. `name1=value1&name2=value2`).

Variable Name (case insensitive)	Type	Description
<b>errorCode</b>	integer	Error code (see list below for possible values).
<i>errorMessage</i>	string	Explanation of error.
<i>errorItem</i>	string	The problematic request parameter (this is relevant to errorCode -2, -3 and -4).

Here are the possible values for "errorCode" and "errorMessage":

errorCode	errorMessage
0	Successful
-1	Request was not made over HTTPS!
-2	'xxxx' is an unrecognized argument!
-3	The 'xxxx' argument is missing!
-4	The value of the 'xxxx' argument is invalid!
-14	An unknown error occurred!
-17	Request used GET rather than POST!