

# !initCustomerSession

Live urls:

<https://secure.sectigo.com/products/!initCustomerSession>

## Version History

1.00 Original version.

This API allows the web host partners create a SASP session for its end customer. This session will allow to redirect end customer to the SASP Post Payment page of his order.

## 1. Request

The request should be POSTed (rather than GETed) to the above URL.

Required variables are in **bold**.

Optional variables are in *italics*.

Variable Name (case insensitive)	Type	Max. Length	Allowed Values	Description
<b>loginName</b>	string	64 chars		Account Username (case sensitive)
<b>loginPassword</b>	string	128 chars		Account Password (case sensitive)
<b>orderNumber</b>	string	64 chars		The Order Number of a certificate for which need open Post Payment page.
<i>responseFormat</i>	char	1 char	<b>0</b> = New-line delimited parameters (default). <b>1</b> = URL-encoded parameters.	Explained in sections 2 and 3 below.

## 2. Response (when *responseFormat=0*, the default)

**MIME Type = text/plain**

Line	Possible Value(s)
Line 1: <i>ErrorCode</i>	0 = Successful -1 = Request was not made over https! -2 = Unrecognized argument! -3 = The 'xxxx' argument is missing! -4 = The value of the 'xxxx' argument is invalid! -14 = An unknown error occurred! -16 = Permission denied! -17 = Request used GET rather than POST! -42 = Call limit reached! Please try again later.

**If errorCode < 0**

Line	Possible Value(s)
Line 2: <i>Error Message</i>	Textual representation of error message. See Status Code Possible Value(s)

**If errorCode = 0**

<b>Line</b>	<b>Possible Value(s)</b>
Line 2: <i>SID</i>	Identifier created SASP session handle (type=string, max size=16 chars)

### 3. Response (when *responseFormat=1*)

**MIME Type = *application/x-www-form-urlencoded***

**bold** when always present.

*italic* when not always present.

<b>Name</b>	<b>Possible Value(s)</b>
<b>errorCode</b>	An integer (see section 2 - "errorCode" - for the possible values).
<i>errorMessage</i>	A string (see section 2 - "errorCode" - for the possible values). This parameter is not present when <i>errorCode=0</i> .
<i>SID</i>	SASP session handle. This parameter is only present when <i>errorCode=0</i> .

### 4. Open SASP Post Payment page

In order to open the SASP Post Payment page you need to redirect to url

<https://secure.sectigo.com/products/postPayment1a?SID=<SID>&orderNumber=<orderNumber>>

where:

<SID> - SASP session handle which was got in result of call API !initCustomerSession.

<orderNumber> - SASP order number for which the SASP session was created